

TECHNICAL DATA

Leddura 2Meet 86"

**LET'S GET
SPECIFIC!**

**Share, inspire, have fun!
With CTOUCH by your side.**

CTOUCH[®]

Product number

- Leddura 2Meet 86" for Skype for Business
- Leddura 2Meet 86" for Teams

11050186
11050286

Touch system

- Touch system: Adaptive touch
- Touch point: 32 Point
- Touch tools: Hands or other solid (soft tip) object
- Accuracy: ±2mm
- Touch Resolution: 32768 x 32768 (pixels)
- Interface: USB 2.0 compatible (full speed) HID compliant, Plug & Play compatible. Backwards compatible with USB 1.1
- Supported OS: Windows, MacOS, Android and Chrome
- Touch driver: Not required for 32 touch points (under Windows); MacOS/OSX needs drivers for gestures.

Panel

- Diagonal size: 85,6" (2174 mm)
- Panel technology: TFT LCD
- Panel resolution: 3840 x 2160
- Frame rate: 60 Hz
- Brightness: 350 cd/m²
- Aspect Ratio: 16:9
- Contrast Ratio (Static): 1200:1
- Contrast Ratio (Dynamic): 5000:1
- Response time: 8 ms
- Display Colours: 1.07 Billion (10 bits)
- Pixel pitch (W x H): 0.4935 x 0.4935 mm
- Viewing Angle: 178° / 178°
- Backlight type: Direct LED
- Service Life: > 30.000 Hours
- Installation: Landscape

Connectivity

- Video input (digital): 3x HDMI 2.0, 1x DP 1.2
- Video input (analog): 1x VGA
- Audio input: 1x Mini Jack
- Audio output: 1x S/PDIF Optical, 1x Mini Jack
- USB: 4x USB 2.0
- Touch: 2x USB-B
- RS232C: 1x DB-9
- LAN port: 1x RJ45 10/100/1000 BaseT
- Connection Bay

Video

- PSM: Warm / Cool / Normal
- Picture Mode: Dynamic / Standard / Soft / User
- Freeze function: Yes
- Backlight mute function: Yes
- Blue Light Filter

Check out the Leddura 2Meet folder for more information.

All rights reserved. CTOUCH products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of CTOUCH Europe B.V.. All other product and service names mentioned are the trademarks of their respective owners. All weights and dimensions are approximate. Product specifications are subject to change without prior notification.

Sound – Designed, tuned and built by HARMAN

- Transducers: 2 Stereo JBL[®] 3-Way Speakers (tweeter, mid-range and woofer)
- Amplifier power: 80 watts
- Frequency range: 60Hz – 20kHz
- JBL[®] LiveStage (Virtual) surround sound
- JBL[®] far-field microphones

Meeting office application

- Embedded integrated meeting software solution based on Skype for Business or Microsoft Teams
- Runs on dedicated Intel OPS i5 PC Module

Features / Convenience

- Gesture recognition: Yes, refer to the CTOUCH manual
- HDCP compliance 2.2
- Thickness of safety glass: 4 mm (hardness Mohs 7)
- Network controllable input: 1x RS232C & 1x LAN IN (over IP)
- Human presence detection
- BRIX compatible: based on a futureproof modular platform

OSD

- Touch OSD: Yes
- OSD Language Function: Dutch, English, French, German, Spanish

Power

- Power Supply: AC 100–240 V 50 / 60Hz
- Power Consumption (in Operation): 189W
- Power Consumption (in Standby): <= 0.5 W
- Ambient light sensor: Yes

Quality approvals

- Regulatory approvals: CE, FCC
- Green approval: Energy Star, RoHS complaint, WEEE
- ISO Standard: ISO9001 and ISO14001

Dimensions & Weight

- Product dimensions (WxHxD): 1991 x 1173 x 113 (mm)
- Product weight: 103 kg
- Vesa Mount (WxH): 800 x 600 (mm), M8 screw

Product accessories

- Accessories pack: power cable, USB cable, HDMI cable, remote control, 2 passive pens, Quick Start Guide & Warranty card

Logistics information

- Box size (WxHxD): 2118 x 1324 x 290 (mm)
- Gross weight: 112 kg
- EAN no.:

8719481480561