

**TECHNICAL DATA**

**CTOUCH Canvas 65"**

**LET'S GET  
SPECIFIC!**

**Share, inspire, have fun!**  
**With CTOUCH by your side.**

**CTOUCH<sup>®</sup>**

## Product number

- CTOUCH Canvas 65" Midnight Grey
- CTOUCH Canvas 65" Electric Blue
- CTOUCH Canvas 65" Regal Orange

**11052565**  
**11062565**  
**11072565**

## CTOUCHABLE™ design

- Patented Canvas Frame: Rugged rubber edge in colours: Regal Orange / Electric Blue / Midnight Grey
- Patented Canvas Frame: Soft-touch textile with integrated touch-able controls
- High-precision 'pen-on-paper' like writing: Optical Bonded InGlass™

## Touch system

- Touch system: FlatFrog InGlass™ Touch
- Touch points: 20
- Touch tools: pen, finger, eraser
- Accuracy: 0.4 mm
- Minimum response size: 2 mm
- Touch resolution: 22.855 x 12.856 (pixels)
- Interface: USB 3.0 compatible HID compliant, Plug & Play compatible. Backwards compatible with USB 2.0 and 1.1
- Supported OS: Windows, macOS, Chrome, Linux and Android
- Touch driver: Not required for Windows and single touch macOS

## Panel

- Diagonal size: 64.53" (1.639 mm)
- Panel technology: TFT LCD, Direct LED Backlight
- Display resolution: 3.840 x 2.160
- Frame rate: 60 Hz
- Brightness: 350 cd/m<sup>2</sup>
- Aspect ratio: 16:9
- Contrast ratio (static): 5.000:1
- Response time (gray to gray): 8 ms
- Display colours: 1.07 Billion (8 bits + FRC)
- Pixel pitch (W x H): 0.372 x 0.372 mm
- Viewing angle: 178° / 178°
- Service life: > 30.000 Hours
- Orientation: landscape

## Glass

- Glass: Triple S Glass (Smooth, Stripeless, Safety)
- Type: heat tempered, anti glare, safety glass
- Thickness: 4 mm
- Hardness: 7 Mohs

## Connectivity

- Video input (digital): 3x HDMI 2.0 (1x ARC), 1x DP 1.2, 1x USB-C (USB 3.1 Gen 2)
- Video input (analog): 1x VGA (including 1x Mini Jack)
- Audio input: 1x Mini Jack (dedicated audio source)
- Audio output: 1x Mini Jack, 1x S/PDIF Optical
- USB: 3x USB 3.0 (type-A), 2x USB 2.0 (type A)
- Touch: 3x USB (type B)
- RS232C: 1x DE-9F

- LAN port: 2x RJ45 10/100/1000 BaseT
- Module-slots: 1x OPS-slot (UHD@60Hz), 1x CTOUCH Slide-in slot, (modules are optional)
- Dedicated ports: 1x NFC Reader port, 1x Fingerprint Scanner port, (modules are optional)

## Designed for Business

- Security-by-design: NO-OS operating system
- Scalability: BRIX solutions modularity
- Sustainability: Product Circularity Passport
- Software license bundle: AirServer screensharing and FlatFrog Board whiteboarding. See software folder for details.

## Video

- Eye comfort: blue light filter
- Colour temperature: warm, cool, normal
- Picture modes: dynamic, standard, soft, user

## Sound: designed, tuned, built by HARMAN

- Transducers: 2 stereo JBL® 3-way speakers
- Amplifier power: 80 Watts
- Frequency range: 60 Hz - 20 kHz
- JBL® LiveStage (Virtual) surround sound
- JBL® 2 far-field microphone array

## OSD

- Languages: Dutch, English, German

## Power

- Power supply: AC 100-240 V 50 / 60 Hz
- Power consumption (in operation): 114 W
- Power consumption (in standby): <= 0.5 W
- Energy label: F

## Quality approvals

- Regulatory approvals: CE, RoHS compliant
- Green approval: WEEE
- ISO Standard: ISO9001 and ISO14001

## Dimensions & Weight

- Product dimensions (W x H x D): 1.525 x 914 x 111 mm
- Product weight: 48.8 kg
- Vesa mount (W x H): 600 x 400 mm, M8 Screw

## Product accessories

- Accessories included: power cable (3 m), USB touch cable (3 m), HDMI cable (3 m), USB-C cable (1 m), remote control (incl. batteries), 2 passive pens, quick start guide & warranty card

## Logistics information

- Box size (W x H x D): 1.637 x 1.067 x 234 mm
- Gross weight: 57.6 kg
- CTOUCH Canvas 65" Midnight Grey
- CTOUCH Canvas 65" Electric Blue
- CTOUCH Canvas 65" Regal Orange

**8719481481445**  
**8719481481452**  
**8719481481469**

## Check out the CTOUCH Canvas folder for more information.

All rights reserved. CTOUCH products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of CTOUCH Europe B.V. All other product and service names mentioned are the trademarks of their respective owners. All weights and dimensions are approximate. Product specifications are subject to change without prior notification.