



Leddura 2Share series

Wireless sharing. With any device.

Leddura 2Share was specially designed to share digital content wirelessly and securely in meeting rooms. It also brings easy access to a digital whiteboard and annotation functionality to make collaboration as easy as can be.

- ✓ Easy to use wireless presentation and collaboration system
- ✓ Wireless sharing with any device
- ✓ Integrated whiteboard and annotation functionality
- ✓ Secure and reliable
- ✓ Unparalleled JBL Live Stage (virtual) surround sound for best sound experience

Product number

- 32 Point touch: 10051875

Touch system

- Touch system: Surface Light Wave
- Touch points: 32 points
- Touch tool: Hand or other solid (soft tip) object
- Accuracy: ± 3 mm
- Read speed: 120 responses per second
- Effective screen size (mm): 1.650,24 (W) x 928,26 (H)
- Interface: USB 1.1 compatible (full speed) HID compliant, Plug & Play compatible, USB 2.0
- Supported OS: Windows, Mac and Android
- Touch driver: Not required for 20 points (under Windows and Android); 32 points need driver (under Windows)

Panel

- Diagonal size: 74.5"
- Panel resolution: 3840 x 2160
- Brightness (Nits): 350 cd/m²
- Contrast ratio: 1200 : 1
- Aspect ratio: 16 : 9
- Display colour: 1.07 Billion colours (10-bit)
- Pixel pitch (mm): 0.4298 (W) x 0.4298 (H)
- Back light unit: Direct LED
- Anti reflective glass: Yes

Connectivity

- Video input (digital): HDMI x 2, DP x 1
- Video input (analogue): VGA IN x 3, AV IN (mini jack) x 1
- Video output: HDMI x 1, VGA OUT x 1
- Audio input: Mini jack x 3, Mic x 1
- Audio output: HDMI out x 1, (SPDIF) x 1
- USB (for touch): USB TypeB x 1, USB 2.0 x 2, USB FW
- Network controllable input: RS232C, LAN IN
- Internal Wireless AC Router: 802.11 a/b/g/n/ac

Sound - Designed, tuned and built by HARMAN

- Transducers: 2 Stereo JBL 3-Way Speakers (tweeter, mid-range and woofer)
- Amplifier power: 80 watts
- frequency range: 60Hz - 20kHz
- JBL Far Field microphone and noise reduction and echo canceling
- JBL LiveStage surround sound

Features / Convenience

FUNCTION

- OSD with Touch: Yes
- Languages: English
- Internal OPS module slot: Yes
- HDCP compliance: 2.2

VIDEO

- PSM: Warm / Cool / Normal
- Picture mode: Dynamic / Standard / Soft / User / Game / Writing
- Energy Mode: Normal / Balanced / Eco friendly / auto adjust
- Freeze function: Yes
- Backlight mute function: Yes
- Ambient light sensor (auto adjust backlight): Yes

Wireless sharing application

- Whiteboard / wireless sharing
- Embedded wireless sharing solution
- Secure and reliable
- Stand alone or seamless integration into your network.
- Crossplatform

Dimensions and Quality approvals

- Dimensions (mm): 1735.6 (W) x 1027.6 (H) x 122 (D)
- Product weight: 86 kg
- VESA mount (mm): 600 (W) x 400 (H)
- Green approvals: RoHS compliant
- Regulatory approvals: CE
- ISO standard: ISO9001 and ISO14001
- Thickness of safety glass: 4 mm

Power consumption

- Power consumption nominal: 163 W
- Power consumption sleep mode: 0.5 W

Warranty

- Service & warranty: 3 years warranty

Product accessories- Included

- Accessories pack: Power cable, USB cable, HDMI cable, remote, touch pen, Quick start guide, Docking station with visitor USB tokens.

Extras

SUPPORT & TRAINING




- Support and training programs: On request

MOUNTING

- CTOUCH Wallom2 wall lift - electric: 10080250
- CTOUCH Wallom2 mobile lift - electric: 10080251

Logistics information

- Box size (mm): 1871 (W) x 1163 (H) x 250 (D)
- Gross weight: 96 kg
- EAN no.: 8719481480110



All rights reserved. CTOUCH products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of CTOUCH Europe B.V.. All other product and service names mentioned are the trademarks of their respective owners.

Specifications CTOUCH Leddura 2Share75 inch (UHD)

www.ctouch.eu